





# TEST REPORT

**Applicant:** DIGIVIEW TECHNOLOGY LIMITED  
**Address of Applicant:** Room 509, 5/F, Tian Shu Block, Xinggang Tongchuanghui,  
No.6099 Baoan District, Shenzhen, Guangdong, China  
**Manufacturer/Factory:** DIGIVIEW TECHNOLOGY LIMITED  
**Address of** Room 509, 5/F, Tian Shu Block, Xinggang Tongchuanghui,  
**Manufacturer/Factory:** No.6099 Baoan District, Shenzhen, Guangdong, China  
**Equipment Under Test (EUT)**  
Product Name: POWER BANK  
Brand Name:   
Model No.: DP50DQ-A  
**Applicable standards:** ETSI EN 303 417 V1.1.1 (2017-09)  
**Date of sample receipt:** November 28, 2023  
**Date of Test:** November 28, 2023 To December 8, 2023  
**Date of report issue:** December 8, 2023  
**Test Result :** Pass \*

\*In the configuration tested, the EUT complied with the standards specified above.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.

Authorized Signature



Kevin Wang

Laboratory Manager





## 2 Version

Version No.	Date	Description
00	December 8, 2023	Original

Prepared By:

Gang Wang

Date:

December 8, 2023

Project Engineer

Reviewed By:

Kevin Wang

Date:

December 8, 2023

Reviewer





### 3 Contents

	Page
1 COVER PAGE .....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
5 GENERAL INFORMATION .....	5
5.1 GENERAL DESCRIPTION OF E.U.T. ....	5
5.2 TEST MODE .....	5
5.3 DESCRIPTION OF SUPPORT UNITS .....	5
5.4 DEVIATION FROM STANDARDS .....	5
5.5 ABNORMALITIES FROM STANDARD CONDITIONS .....	5
5.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	5
6 TEST INSTRUMENTS LIST .....	6
7 RADIO SPECTRUM MATTER TEST RESULTS .....	7
7.1 OPERATING FREQUENCY RANGE(S) (OFR) .....	7
7.2 H-FIELD .....	8
7.3 TRANSMITTER OUT OF BAND(OOB) EMISSIONS .....	10
7.4 TRANSMITTER SPURIOUS EMISSIONS .....	12
7.5 RECEIVER BLOCKING .....	15
8 EUT CONSTRUCTIONAL DETAILS .....	15



## 4 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Operating frequency range(s) (OFR)	EN 303 417 V1.1.1	EN 303 417 V1.1.1 Clause 6.2.1	EN 303 417 V1.1.1 Clause 4.3.3	Pass
H-field	EN 303 417 V1.1.1	EN 303 417 V1.1.1 Clause 6.2.1	EN 303 417 V1.1.1 Clause 4.3.4	Pass
Transmitter spurious emissions	EN 303 417 V1.1.1	EN 303 417 V1.1.1 Clause 6.2.1	EN 303 417 V1.1.1 Clause 4.3.5	Pass
Transmitter out of band (OOB) emissions	EN 303 417 V1.1.1	EN 303 417 V1.1.1 Clause 6.2.1	EN 303 417 V1.1.1 Clause 4.3.6	Pass
Receiver blocking	EN 303 417 V1.1.1	EN 303 417 V1.1.1 Clause 6.3.2	EN 303 417 V1.1.1 Clause 4.4.2	Pass



## 5 General Information

### 5.1 General Description of E.U.T.

Product Name:	POWER BANK
Model No.:	DP50DQ-A
Operation Frequency:	100-300kHz
Modulation type:	ASK
Antenna Type:	Coil Antenna
Antenna Gain:	0dBi
Power Supply:	USB-C Input: 5V $\overline{\text{---}}$ 2.4A Battery: 3.7V, 5000mAh, 18.5Wh USB-C Output: 5V $\overline{\text{---}}$ 2.4A USB-A Output: 5V $\overline{\text{---}}$ 2.4A USB-A & USB-C Output: 5V $\overline{\text{---}}$ 2.4A Wireless output: 5W

### 5.2 Test mode

Operating mode	Keep the EUT in operating mode
Standby mode	Keep the EUT in idle mode.

### 5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
HUAWEI	Mobile Phone	P40	N/A

### 5.4 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.
---

### 5.5 Abnormalities from Standard Conditions

None.
-------

### 5.6 Other Information Requested by the Customer

None.
-------



## 6 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Jul. 2 2022	Jul. 1 2025
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jun. 27 2023	Jun. 26 2024
4	BiConiLog Antenna	SCHWARZBECK MESS- ELEKTRONIK	VULB9163	GTS214	Jun. 27 2023	Jun. 26 2024
5	Double -ridged waveguide horn	SCHWARZBECK MESS- ELEKTRONIK	BBHA 9120 D	GTS208	Jun. 27 2023	Jun. 26 2024
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	Jun. 27 2023	Jun. 26 2024
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	Jun. 27 2023	Jun. 26 2024
9	Coaxial Cable	GTS	N/A	GTS211	Jun. 27 2023	Jun. 26 2024
10	Coaxial cable	GTS	N/A	GTS210	Jun. 27 2023	Jun. 26 2024
11	Coaxial Cable	GTS	N/A	GTS212	Jun. 27 2023	Jun. 26 2024
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jun. 27 2023	Jun. 26 2024
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	Jun. 27 2023	Jun. 26 2024
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Jun. 27 2023	Jun. 26 2024
15	Band filter	Amindeon	82346	GTS219	Jun. 27 2023	Jun. 26 2024
16	Power Meter	Anritsu	ML2495A	GTS540	Jun. 27 2023	Jun. 26 2024
17	Power Sensor	Anritsu	MA2411B	GTS541	Jun. 27 2023	Jun. 26 2024
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jun. 27 2023	Jun. 26 2024
19	Splitter	Agilent	11636B	GTS237	Jun. 27 2023	Jun. 26 2024
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	Jun. 27 2023	Jun. 26 2024
21	Breitband hornantenne	SCHWARZBECK	BBHA 9170	GTS579	Jun. 27 2023	Jun. 26 2024
22	Amplifier	TDK	PA-02-02	GTS574	Jun. 27 2023	Jun. 26 2024
23	Amplifier	TDK	PA-02-03	GTS576	Jun. 27 2023	Jun. 26 2024
24	PSA Series Spectrum Analyzer	Rohde & Schwarz	FSP	GTS578	Jun. 27 2023	Jun. 26 2024

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	Jun. 27 2023	Jun. 26 2024
2	Barometer	ChangChun	DYM3	GTS255	Jun. 27 2023	Jun. 26 2024

EBO assures objectivity and justness of the test, and fulfill the duty of confidentiality for applicant's information. Applicant should undertake responsibility for the authenticity of submitted sample and information. The result(s) shown in this report refer only to the sample(s) tested. The test results only reflect the evaluation of the sample under test and are not authorized for other purposes. EBO do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise. This report is invalid without signatures of approver and special seal for inspection of EBO, or it has been reproduced in full or part. This report shall not be published as advertisement without the approval of EBO. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This document is issued by the company under its General Conditions of Service accessible at <http://www.ebotest.com/zjyb/318.html>.

## 7 Radio Spectrum Matter Test Results


### 7.1 Operating frequency range(s) (OFR)

Test Requirement:	ETSI EN303 417 Clause 4.3.3					
Test Method:	ETSI EN303 417 Clause 6.2.1					
Receiver setup:	<ul style="list-style-type: none"> <li>• Start frequency: lower than the lower edge of the permitted frequency range / requested by the essential requirements in clause 4.3.3.</li> <li>• Stop frequency: higher than the upper edge of the permitted frequency range / requested by the essential requirements in clause 4.3.3.</li> <li>• Resolution Bandwidth: see ETSI EN 300 330 [1], clause 5.12, Table 11.</li> <li>• Video Bandwidth: &gt; Resolution bandwidth.</li> <li>• Detector mode: see ETSI EN 300 330 [1], clause 5.12, Table 11.</li> <li>• Display mode: Max. hold.</li> <li>• Sweep time: the sweep time shall be chosen in such a way that the time of each sub-operational mode / operational mode (WPT system operation cycle) is taken into account.</li> </ul>					
Limit:	Operating frequency range for emissions shall be within one of the following limits: 19 - 21 kHz, 59 - 61 kHz, 79 - 90 kHz, 100 - 300 kHz, 6 765 - 6 795 kHz.					
Test setup diagram:	 <pre> graph LR     A[Input from Test Fixture] --&gt; B[Measuring Receiver]     B --&gt; C[Data Store]             </pre>					
Test Instruments:	Refer to section 6 for details					
Test mode:	Operating mode					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Measurement Record:	Uncertainty: $\pm 1 \times 10^{-7}$					

#### Measurement Data:


Measurement Conditions		$f_L$ (kHz)	$f_H$ (kHz)	Limit (kHz)	Result
Tnormal (24°C)	Vnor: 5.0V dc	110.2	204.6	100-300	PASS

## 7.2 H-field

Test Requirement:	ETSI EN303 417 Clause 4.3.4																														
Test Method:	ETSI EN303 417 Clause 6.2.1																														
Test site:	Measurement Distance: 3m																														
Limit:	<div>Table 3: H-field limits</div> <table><tr><th>Frequency range [MHz]</th><th>H-field strength limit [dBµA/m at 10 m]</th><th>Comments</th></tr><tr><td><math>0,019 \leq f &lt; 0,021</math></td><td>72</td><td></td></tr><tr><td><math>0,059 \leq f &lt; 0,061</math></td><td>69,1 descending 10 dB/dec above 0,059 MHz</td><td>See note 1</td></tr><tr><td><math>0,079 \leq f &lt; 0,090</math></td><td>67,8 descending 10 dB/dec above 0,079 MHz</td><td>See note 2</td></tr><tr><td><math>0,100 \leq f &lt; 0,119</math></td><td>42</td><td></td></tr><tr><td><math>0,119 \leq f &lt; 0,135</math></td><td>66 descending 10 dB/dec above 0,119 MHz</td><td>See note 1</td></tr><tr><td><math>0,135 \leq f &lt; 0,140</math></td><td>42</td><td></td></tr><tr><td><math>0,140 \leq f &lt; 0,1485</math></td><td>37,7</td><td></td></tr><tr><td><math>0,1485 \leq f &lt; 0,30</math></td><td>-5</td><td></td></tr><tr><td><math>6,765 \leq f &lt; 6,795</math></td><td>42</td><td></td></tr></table> <div><div>NOTE 1: Limit is 42 dBµA/m for the following spot frequencies: 60 kHz ± 250 Hz and 129,1 kHz ± 500 Hz.</div><div>NOTE 2: At the time of preparation of the present document the feasibility of increased limits for high power wireless power transmission systems to charge vehicles [i.4] was prepared. New specific requirements for such systems (e.g. higher H-field emission limits in the 79 - 90 kHz band) will be reflected within a future revision of the present document.</div></div>	Frequency range [MHz]	H-field strength limit [dBµA/m at 10 m]	Comments	$0,019 \leq f < 0,021$	72		$0,059 \leq f < 0,061$	69,1 descending 10 dB/dec above 0,059 MHz	See note 1	$0,079 \leq f < 0,090$	67,8 descending 10 dB/dec above 0,079 MHz	See note 2	$0,100 \leq f < 0,119$	42		$0,119 \leq f < 0,135$	66 descending 10 dB/dec above 0,119 MHz	See note 1	$0,135 \leq f < 0,140$	42		$0,140 \leq f < 0,1485$	37,7		$0,1485 \leq f < 0,30$	-5		$6,765 \leq f < 6,795$	42	
Frequency range [MHz]	H-field strength limit [dBµA/m at 10 m]	Comments																													
$0,019 \leq f < 0,021$	72																														
$0,059 \leq f < 0,061$	69,1 descending 10 dB/dec above 0,059 MHz	See note 1																													
$0,079 \leq f < 0,090$	67,8 descending 10 dB/dec above 0,079 MHz	See note 2																													
$0,100 \leq f < 0,119$	42																														
$0,119 \leq f < 0,135$	66 descending 10 dB/dec above 0,119 MHz	See note 1																													
$0,135 \leq f < 0,140$	42																														
$0,140 \leq f < 0,1485$	37,7																														
$0,1485 \leq f < 0,30$	-5																														
$6,765 \leq f < 6,795$	42																														
<div>Limit for measurement at 3m distance</div> <div>The H-field limit in dBµA/m at 3 m, <math>H_{3m}</math>, is determined by the following equation:</div> <div><div><div><math display="block">H_{3m} = H_{10m} + C_3</math></div><div>(H.2)</div></div></div> <div>where:</div> <div><div><math>H_{10m}</math> is the H-field limit in dBµA/m at 10 m distance according to the present document; and</div><div><math>C_3</math> is a conversion factor in dB determined from figure H.2.</div></div> <div><div>Correction factor, <math>C_3</math>, for limits at 3 m distance, dB</div><div></div></div> <div>Figure H.2: Conversion factor <math>C_3</math> versus frequency</div>																															



Test setup diagram:



Test Instruments:

Refer to section 6.0 for details

Test mode:

Operating mode

Test environment:

Temp.: 25 °C Humid.: 52% Press.: 1 012mbar




Measurement Record:

Uncertainty:  $\pm 4.5\text{dB}$ 

Measurement Data:

Frequency (kHz)	Measured Level (dB $\mu$ A/m at 3m)	Limit (dB $\mu$ A/m at 10m)	Conversion factor C3	Limit (dB $\mu$ A/m at 3m)	Result
124.5	14.34	42	31.2	73.2	Pass

### 7.3 Transmitter out of band(OOB) emissions

Test Requirement:	ETSI EN303 417 Clause 4.3.6
Test Method:	ETSI EN303 417 Clause 6.2
Limit:	 <p>Figure 4: Out of band and spurious domain of a single frequency WPT system</p>  <p>Figure 5: Out of band and spurious domain of a multi - frequency system (during one WPT system cycle time)</p>
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Measurement Record:	Uncertainty: $\pm 1 \times 10^{-7}$

EBO assures objectivity and justness of the test, and fulfill the duty of confidentiality for applicant's information. Applicant should undertake responsibility for the authenticity of submitted sample and information. The result(s) shown in this report refer only to the sample(s) tested. The test results only reflect the evaluation of the sample under test and are not authorized for other purposes. EBO do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise. This report is invalid without signatures of approver and special seal for inspection of EBO, or it has been reproduced in full or part. This report shall not be published as advertisement without the approval of EBO. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This document is issued by the company under its General Conditions of Service accessible at <http://www.ebotest.com/zjyb/318.html>.



Shenzhen EBO Testing Center

Tel: +86-755-33126608

Email :ebo@ebotest.com Web :www.ebotest.com

Report No.: EBO2312008-E018

Report Version: 1.0


Page 11 of 15


#### **Measurement Data:**

For the H-Field emission is below the unwanted radiated emissions limit, the OOB test result complied with the OOB requirement.

EBO assures objectivity and justness of the test, and fulfill the duty of confidentiality for applicant's information. Applicant should undertake responsibility for the authenticity of submitted sample and information. The result(s) shown in this report refer only to the sample(s) tested. The test results only reflect the evaluation of the sample under test and are not authorized for other purposes. EBO do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise. This report is invalid without signatures of approver and special seal for inspection of EBO, or it has been reproduced in full or part. This report shall not be published as advertisement without the approval of EBO. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This document is issued by the company under its General Conditions of Service accessible at <http://www.ebotest.com/zjyb/318.html>.

## 7.4 Transmitter spurious emissions

Test Requirement:	ETSI EN303 417 Clause 4.3.5																		
Test Method:	ETSI EN303 417 Clause 6.2.1																		
Limit:	<div>Table 4</div> <table><tr><th>State (see note)</th><th>Frequency 9 kHz ≤ f &lt; 10 MHz</th><th>Frequency 10 MHz ≤ f &lt; 30 MHz</th></tr><tr><td>Operating</td><td>27 dBμA/m at 9 kHz descending 10 dB/dec</td><td>-3,5 dBμA/m</td></tr><tr><td>Standby</td><td>5,5 dBμA/m at 9 kHz descending 10 dB/dec</td><td>-25 dBμA/m</td></tr></table> <div>NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.</div> <div>The power of any radiated spurious emission between 30 MHz and 1 GHz shall not exceed the values given in Table</div> <div>Table 5</div> <table><tr><th>State (see note)</th><th>47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz</th><th>Other frequencies between 30 MHz to 1 000 MHz</th></tr><tr><td>Operating</td><td>4 nW</td><td>250 nW</td></tr><tr><td>Standby</td><td>2 nW</td><td>2 nW</td></tr></table> <div>NOTE: "Operating" means mode 2, 3 and 4 according to Table 2; "standby" means mode 1 according to Table 2.</div> <div>Limit for measurement at 3m distance</div> <div>The H-field limit in dBμA/m at 3 m, <math>H_{3m}</math>, is determined by the following equation:</div> <div><math display="block">H_{3m} = H_{10m} + C_3</math><div>(H.2)</div></div> <div>where:</div> <div><math>H_{10m}</math> is the H-field limit in dBμA/m at 10 m distance according to the present document; and</div> <div><math>C_3</math> is a conversion factor in dB determined from figure H.2.</div> <div><div>Correction factor, <math>C_3</math>, for limits at 3 m distance, dB</div></div> <div>Figure H.2: Conversion factor <math>C_3</math> versus frequency</div>	State (see note)	Frequency 9 kHz ≤ f < 10 MHz	Frequency 10 MHz ≤ f < 30 MHz	Operating	27 dBμA/m at 9 kHz descending 10 dB/dec	-3,5 dBμA/m	Standby	5,5 dBμA/m at 9 kHz descending 10 dB/dec	-25 dBμA/m	State (see note)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz	Other frequencies between 30 MHz to 1 000 MHz	Operating	4 nW	250 nW	Standby	2 nW	2 nW
State (see note)	Frequency 9 kHz ≤ f < 10 MHz	Frequency 10 MHz ≤ f < 30 MHz																	
Operating	27 dBμA/m at 9 kHz descending 10 dB/dec	-3,5 dBμA/m																	
Standby	5,5 dBμA/m at 9 kHz descending 10 dB/dec	-25 dBμA/m																	
State (see note)	47 MHz to 74 MHz 87,5 MHz to 118 MHz 174 MHz to 230 MHz 470 MHz to 790 MHz	Other frequencies between 30 MHz to 1 000 MHz																	
Operating	4 nW	250 nW																	
Standby	2 nW	2 nW																	

Test setup diagram:						
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Operating mode					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar
Measurement Record:	Uncertainty: 4.64dB					

EBO assures objectivity and justness of the test, and fulfill the duty of confidentiality for applicant's information. Applicant should undertake responsibility for the authenticity of submitted sample and information. The result(s) shown in this report refer only to the sample(s) tested. The test results only reflect the evaluation of the sample under test and are not authorized for other purposes. EBO do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise. This report is invalid without signatures of approver and special seal for inspection of EBO, or it has been reproduced in full or part. This report shall not be published as advertisement without the approval of EBO. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This document is issued by the company under its General Conditions of Service accessible at <http://www.ebotest.com/zjyb/318.html>.




**Measurement Data:**

Freq (MHz)	Spurious Emission Level@3m(dBuA/m)	Limit(dBuA/m) @3m	Conversion factor C3	Limit(dBuA/m) @10m	Over Limit
0.14	23.29	46.81	31.20	15.61	-23.52
0.16	15.04	45.49	31.20	14.29	-30.45
0.25	13.64	43.53	31.20	12.33	-29.89
0.36	18.32	42.28	31.20	11.08	-23.95
0.52	27.04	40.19	31.00	9.19	-13.15
0.94	21.21	37.18	30.50	6.68	-15.97

Freq (MHz)	Spurious Emission Level(dBm/m)	Limit Line (dBm/m)	Over Limit (dB)	Polarity
33.92	-70.00	-36	-34.00	V
49.66	-65.96	-54	-11.96	V
76.26	-61.24	-36	-25.24	V
172.48	-66.08	-54	-12.08	V
226.22	-67.31	-54	-13.31	V
318.74	-57.48	-36	-21.48	V
34.92	-70.68	-36	-34.68	H
185.82	-68.33	-54	-14.33	H
320.98	-62.09	-36	-26.09	H
358.28	-55.51	-36	-19.51	H
567.14	-65.63	-54	-11.63	H
884.93	-53.46	-36	-36.50	H

## 7.5 Receiver blocking

Test Requirement:	ETSI EN303 417 Clause 4.4.2																									
Test Method:	ETSI EN303 417 Clause 6.3.2																									
Limit:	<table><tr><th colspan="4">Table 6: Receiver blocking limits</th></tr><tr><th></th><th>In-band signal</th><th>OOB signal</th><th>Remote-band signal</th></tr><tr><td>Frequency</td><td>Centre frequency (<math>f_c</math>) of the WPT system (see clause 4.3.3)</td><td><math>f = f_c \pm F</math> (see note)</td><td><math>f = f_c \pm 10 \times F</math> (see note)</td></tr><tr><td>Signal level field strength at the EUT</td><td>72 dB<math>\mu</math>A/m</td><td>72 dB<math>\mu</math>A/m</td><td>82 dB<math>\mu</math>A/m</td></tr><tr><td colspan="4">NOTE: F = OFR see clause 4.3.3.</td></tr></table>						Table 6: Receiver blocking limits					In-band signal	OOB signal	Remote-band signal	Frequency	Centre frequency ( $f_c$ ) of the WPT system (see clause 4.3.3)	$f = f_c \pm F$ (see note)	$f = f_c \pm 10 \times F$ (see note)	Signal level field strength at the EUT	72 dB $\mu$ A/m	72 dB $\mu$ A/m	82 dB $\mu$ A/m	NOTE: F = OFR see clause 4.3.3.			
Table 6: Receiver blocking limits																										
	In-band signal	OOB signal	Remote-band signal																							
Frequency	Centre frequency ( $f_c$ ) of the WPT system (see clause 4.3.3)	$f = f_c \pm F$ (see note)	$f = f_c \pm 10 \times F$ (see note)																							
Signal level field strength at the EUT	72 dB $\mu$ A/m	72 dB $\mu$ A/m	82 dB $\mu$ A/m																							
NOTE: F = OFR see clause 4.3.3.																										
Test setup diagram:	<div><p>WPT system in operational mode <math>\rightarrow</math> e.g. in mode 3 or 4 (see clause 6.1)</p><p>current clamp</p><p>test cable-loop</p><p>air-gap</p><p>Signal generator</p><p>RX – part of the WPT-system (mode dependent)</p><p><math>X=0</math></p><p><math>\Delta R = 0.75m</math></p></div>																									
Test Instruments:	Refer to section 6.0 for details																									
Test mode:	Operating mode																									
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar																				
Measurement Record:	Uncertainty: N/A																									

### Measurement Data:

For each test frequency the "reaction" of the device be recorded and checked against the performance criterion. The WPT system meets the wanted performance criterion at all times, So the test is passed.

## 8 EUT Constructional Details

Reference to the test report No. EBO2312008-E017

-----End-----